Pela	777		OFFER		ORDER	Date:
CUSTOMER	: <u></u>				Elevator refer	ence:
Quantity:		- Control panel type:	1 Speed 2 Speed Hydraulic	Doors:	Manual Automatic Autom. (Only cabir	Shaft lenght.[m] Min. H. betw. Floors n) Speed m/s
Stops number:			VVVF only open loo VVVF open or closed Acces number:	d loop -	MITSUBISHI FRD-7	700 Services number:
· —						
Manoeuvre:		Universal Simplex Duplex Triplex Quadruplex	Down collective Down collective Down collective Down collective		Full collective Full collective Full collective Full collective	
Brake supply Vdc: Manoeuvre circuit Vdc:						
Retiring cams N°:		Retiring cam supply	y Vdc:	Elettrovalves s	upply Vdc:	Emerg. Electrovalve supply Vdc:
Emergency operation		Only descent descent and opening do	oor		Emergenzamatic p	predisposition
<u> </u>		Vac		Three-phase	Single phase	With Vdc deceleration
Doors operator		Vdc	Model:		_	Power ON during run
Opera		tor 1 opening at floor	_	Operator 2 ope	ning at floor	Opening selective simultaneous
Hydraulic Unit		OMAR GMV MORIS 2MC TULFER OTHER:			Starting type:	direct-on-line direct with motorized valve Star-delta with Soft Starter with Soft Starter and star-delta elettrovalve Soft Stop
Motor	Kw Vac In	A	► Three-phase	Single phase	Motor protection	Traction motor with thermistor HT sensor [A] Traction motor
Cabin signalization com + Encoder display :	Vdc Type		position collective direction overload gong Lift-attendant emergency light Speech synt. predispos	Floor signalization	present busy confirmation control out of service collective direction gong main floor position	
Photocell	Vac				all floors position	
Fireman operation key in cabin	with	with return at floor:				EN 81-1/2 EN81-1/2 + A3
Door parking		Open Close				EN 81-20/50 EN 81-70 EN 81-72 EN 81-73
Forced ventila	ation Va	Automatic return at flo	single phase	Three-phase		for machine room
Torcea ventuation va			without HT sensor	Till ee-pilase		Control panel size for pump. unit cabinet
		Phone dialer. Land line Phone dialer. GSM	\Rightarrow	Cabin speakerph machine room te		Cabin roof speakerphone only alarm filter pit alarm push button
		encoder predisp.	encoder 1000 imp/g		Ambient thermos	stat
		movable floor	full load	30 Kg		Pelazza S. r. I reserved space
DELIVERY DATE :		Drawings older	shielded power cabl	e 6 mmq Mt :		Total Price: €
NOTE:						